

M SEALS

THERMEX™ *Gasket Tape & Joint Sealant*



Style 482

- ◆ Resists blowout in high temperature flanges
- ◆ Versatile sealing applications
- ◆ Resists galvanic corrosion with stainless flanges
- ◆ High-strength continuous length of gasketing
- ◆ Easy installation
- ◆ Quality construction
- ◆ Pressure-sensitive adhesive backing
- ◆ Zero waste

Danmark

M Seals A/S
Bybjergvej 13
DK-3060 Espergærde
Telefon: +45 49130205
Fax: +45 49130141
Mail: Sales@m-seals.dk
Web: www.m-seals.dk

Sverige

M Seals A/S
Montörgatan 7
302 60 Halmstad
Telefon: +46 35 15 89 40
Fax: +46 35 12 19 47
Mail: Sales@m-seals.se
Web: www.m-seals.se

M SEALS

UTEX's THERMEX™, Style 482, takes advantage of the latest technology in exfoliated graphite material to provide a high-temperature, high-pressure gasket tape. The manufacturing process of this unique tape provides a high-strength, sure-sealing gasket tape which resists blowout in high-temperature flanges and also resists galvanic corrosion with stainless flanges.

**Thermex is a trademark of UTEX Industries, Inc. (Patent Pending)*

APPLICATIONS

- Steam
- Waste Liquids
- Sewage
- Air
- Gases

SUITABLE USES

- All steel and some composite pipe flanges
- Fume ducts
- Lids
- Heat exchangers
- Most types of housing and vessel flanges



Tex-Cut™ Packing Cutter is also available from UTEX Industries, Inc.

EASY INSTALLATION*

- Using your Tex-Cut™ Packing Cutter*, cut the THERMEX™ packing the length needed.
- Remove the pressure sensitive adhesive from the back of the tape and wrap the tape around the flange.
- Cross the ends of the joint for a quick and simple gasket sealing.

**Cuts at 45° and 90° angles*

SERVICE LIMITS

pH Range	1-14
Temperature Limits	1200°F (649°C) in steam 850°F (454°C) in air
Pressure Limit	1000 psi/69 bar/70.3 kg/cm ²
Max PT, Pressure @ Temp	500 psi @ 500°F 34.5 bar @ 260°C 35.15 kg/cm ² @ 260°C

RECOMMENDED / AVAILABLE SIZES

Flange Sizes	Style 482 Size
Pipes up to 1" dia.	3/16" x 1/8"
1" to 2"	1/4" x 1/8"
2" to 4"	5/16" x 3/16"
4" to 8"	3/8" x 3/16"
8" to 16"	1/2" x 3/16"
16" to 24"	5/8" x 1/4"
24" to 48"	3/4" x 1/4"

PHYSICAL PROPERTIES

Density	109 lbs/cu ft, 1.76 g/cm ³
---------	---------------------------------------